

# Collection Alexia

Artificial leather PU collection

Technical data sheet Alexia

<u>GENERAL</u>		
Composition	50% PL + 50% PU	
Roll width	140cm	
Roll length	+/- 25m	
Weight	520 gr/m <sup>2</sup>	
Thickness	1-1,1mm	
<u>TESTS</u>	<u>METHOD</u>	<u>RESULT / U.M.</u>
Hidrolisis resistance (>100.000 cycles, > 5 years)	UNI 4818-29 / 4818-13	no damage
Bally test (>100.000 cycles) after thermal stress	UNI 4818-13 + PDP 171	no damage
Fastness to light	UNI EN ISO 105 B 02	6/7 – blue scale
Color fastness to water, sea water, swimming pool water, alkaline sweat, spotting acid, spotting alkali	UNI EN ISO 105 E01, 105 B04, 105 E04, 105 E05, 105 E06	5
Martindale abrasion	UNI EN ISO 12947-2	+100.000 rubs
Burning behaviour	EN 1021 I+II, BS 5852 I+II	pass
<u>CERTIFICATS</u>		
REACH COMPLIANT		
SOLVENT FREE		
100% ENVIRONMENT FRIENDLY, 100% HEALTH SAFETY		
<u>CLEANING INSTRUCTIONS</u>		
EASY CLEAN		
<u>REMARKS</u>		
***INTENSIVE DOMESTIC, INDUSTRIAL AND CONTRACT USE		
Slight color differences between production batches can occur.		
The test results only apply to the samples tested.		
Buvetex can't be kept liable for inappropriate use of the artificial leather.		